

ImagePerfect™ 5901 Whiteboard Film incorporates a white, high gloss film that is laminated with a highly transparent polyester, providing a supreme dry-wipe surface that is usable with most brands of dry-wipe pen.

IP 5901

ImagePerfect™ 5901 Whiteboard Film incorporates a high-gloss white PVC with an in-built polyester laminate that is suitable for use with whiteboard/dry-wipe markers. It has been specially created for use in transforming surfaces into whiteboards and for recovering existing whiteboard surfaces. The adhesive has a low initial bond to enable repositionability but builds over 24 hours to form a permanent, waterproof bond on most substrates. It can be cleaned with any whiteboard wiper or IP Surface Cleaner.

| Specifications | |
|------------------------|---|
| DESCRIPTION | Vinyl with a polyester laminate |
| COLOUR | White high gloss |
| THICKNESS | 145 μ |
| WEIGHT | N/A |
| ADHESIVE | Solvent based acrylic, permanent |
| ADHESIVE STRENGTH | 20N / 25mm (Finat TM 1/24h) |
| RELEASE PAPER | PE-coated silicone paper, 140g/m ² |
| TEMPERATURE RANGE | -30°C to +90°C |
| DURABILITY (UNPRINTED) | External, 3 years Internal, 5 years |
| FLAME RETARDANCY | B1 |
| SHELF LIFE | 2 years, 20°C / 50% humidity |

© May 2016 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.